

**Texdecor - Casamance**  
**2, rue d'Hem**  
**59780 WILLEMS**  
**France**

**Your notice of**  
06-03-2024

**Your reference**

**Date**  
04-04-2024

## Analysis Report 24.01300.18

Required tests :

**UK Furniture and Furnishings  
(Fire) (Safety) regulations (1988)  
No. 1324**

**UK Furniture and Furnishings  
(Fire) (Safety) regulations (1988)  
No. 1324**

**The Furniture and Furnishings (Fire) (Safety) regulations :  
1988 No. 1324 - Schedule 4 part I – The cigarette test - BS 5852  
part 1 (1979)**

**The Furniture and Furnishings (Fire) (Safety) regulations :  
1988 No. 1324 - Schedule 5 part I – The match test - BS 5852  
part 1 (1979)**

| Sample id | Information given by the client | Date of receipt |
|-----------|---------------------------------|-----------------|
| T2404972  | 3347-3348-1242-3776-768         | 06-03-2024      |


Gina Créelle  
Order responsible

This report may be reproduced, as long as it is presented in its entire form, without written permission of Centexbel.  
The results of the analysis cover the received samples. Centexbel is not responsible for the representativeness of the samples.  
In assessing compliance with the specifications, we did not take into account the uncertainty on the test results.

## Samples

T2404972  
3347-3348-1242-3776-768





**Reference:** T2404972 - 3347-3348-1242-3776-768


**The Furniture and Furnishings (Fire) (Safety) regulations : 1988 No. 1324 - Schedule 4 part I – The cigarette test - BS 5852 part 1 (1979)**

Date of ending the test 27-03-2024  
 Standard used UK Furniture and Furnishings (Fire) (Safety) regulations (1988) No. 1324  
 Deviation from the standard -  
 Conditioning 23°C, relative humidity 50%  
 Based on information given by the client: specimens have not been cleaned  
 Filling T 23140 (Recticel) \* - non-fire retardant foam - ± 22 kg/m<sup>3</sup>  
 \* The filling complies with the requirements as indicated in schedule 5 part 1 of the UK Furniture and Furnishings (Fire) (Safety) Regulations 1988

|  | 1            | 2            |
|--|--------------|--------------|
| <b>Smouldering criteria</b>            |              |              |
| Unsafe escalating combustion           | no           | no           |
| Test assembly consumed                 | no           | no           |
| Smoulders to extremities               | no           | no           |
| Smoulders through thickness            | no           | no           |
| Smoulders more than 1 hour             | no           | no           |
| Final examination / active smouldering | no           | no           |
| <b>Flaming criteria</b>                |              |              |
| Occurrence of flames                   | no           | no           |
|  |              |              |
|  | non-ignition | non-ignition |

**Conclusion Pass**

The following test results relate only to the ignitability of the combination of materials under the particular conditions of test ; they are not intended as a means of assessing the full potential fire hazard of the materials in use.



**Reference:** T2404972 - 3347-3348-1242-3776-768

**The Furniture and Furnishings (Fire) (Safety) regulations : 1988 No. 1324 - Schedule 5 part I – The match test - BS 5852 part 1 (1979)**

Date of ending the test 27-03-2024  
Standard used UK Furniture and Furnishings (Fire) (Safety) regulations (1988) No. 1324

Deviation from the standard -

Conditioning 23°C, relative humidity 50%

Based on information given by the client: specimens have not been cleaned

Filling T 23140 (Recticel) \* - non-fire retardant foam -  $\pm 22 \text{ kg/m}^3$

\* The filling complies with the requirements as indicated in schedule 5 part 1 of the UK Furniture and Furnishings (Fire) (Safety) Regulations 1988

Flame application time (s) 20

|  | 1            | 2            |
|--|--------------|--------------|
| <b>Smouldering criteria</b>            |              |              |
| Unsafe escalating combustion           | no           | no           |
| Test assembly consumed                 | no           | no           |
| Smoke/heat/glowing more than 15 min    | no           | no           |
| Final examination / active smouldering | no           | no           |
| <b>Flaming criteria</b>                |              |              |
| Unsafe escalating combustion           | no           | no           |
| Test assembly consumed                 | no           | no           |
| Flaming > 120 s                        | no           | no           |
| Afterflame time (s)                    | 0            | 0            |
|  |              |              |
|  | non-ignition | non-ignition |

**Conclusion Pass**

The following test results relate only to the ignitability of the combination of materials under the particular conditions of test ; they are not intended as a means of assessing the full potential fire hazard of the materials in use.